

PRODUCT INFORMATION

CEMENT SOFTENER

ACIDIC BASED

- Features** : Fast acting deep penetrating to dissolve into cement.
- Safe guard against metal corrosion through anti-corrosion compounds.
- Widely used to remove cement (left behind by construction worbers) on mosaic and other ceramic tiles.
- Uses** : Mostly used in commercial buildings, households and factories to soften and subsequently remove cement.
- Directions** : Apply adequate quantity to the unwanted cement and allow to react for 1-2 minutes. Larger blocks require longer time. Scrap off with a scraper and flush with water.
- Care must be taken to avoid damaging the grouts and the tiles when using product. If the cement occurs as small blocks, use a cloth moistened with cement softener and allow to come into contact for 2-3 minutes before scraping. This will minimise damage to the tiles and grouts.
- Specifications** :
- | | |
|------------------|-----------------------------------|
| Appearance | : Clear light brown liquid. |
| pH (1% solution) | : 1.0 - 2.0 |
| Sg | : 1.09-1.11 @ 26 °C |
| Odour | : Sharp penetrating sourish odour |
| Shelf-life | : 1 year in good conditions. |
- Warning** : Avoid contact with eyes, skin and clothing.
Always wear gloves while handling.
Harmful if swallowed.



Distributor :
OCI SUPPLY SDN BHD
2018 0103 9495 (1301526-T)
22, JALAN 8/91, TAMAN SHAMELIN
PERKASA, JALAN CHERAS,
56100 KUALA LUMPUR, MALAYSIA.
TEL: +603 9283 9000
FAX: +603 9285 7570
EMAIL: sales1@ocisupply.com.my



Manufacturer:
OGOSIN CHEMICAL INDUSTRIES SDN BHD
1995 0103 0946 (360152 U)
No 11 Jalan Lombong Emas 4
Seremban Light Industrial Park
Jalan Tun Dr Ismail
70200 Seremban
Negeri Sembilan
Tel: 606-7611899 Fax : 606-7619819