

PRODUCT INFORMATION

MIRAGLOSS

FLOOR FINISH & SEALER

- Description** : **MIRAGLOSS** is a high solids metallised thermal-plastic styrene-acrylic polymers designed to provide the maximum in durability and economy. The film provided by **MIRAGLOSS** is clear, flexible and tough. It is easily dry buffed to a "wet-look" gloss.
- Features** : 1) Hard, tough, brilliant, super-clean gloss straight off the mop.
2) Good flow and leveling.
3) Extra durability, resistance to black heel marking and wearing. Hence less spray buffing and recoating.
4) Excellent water and chemical resistance.
5) Fast drying
6) Good reparability - surface marks easily removed, recoated and repaired.
- Uses** : **MIRAGLOSS** is designed for use on all resilient and non-resilient floor, vinyl, vinyl asbestos, asphalt rubber tile etc, as well as terrazzo, marble, quarry tile, concrete and sealed wood floor.
- Directions** : Sweep the floor. Scrub the floor with **MIRASTRIP** to removal all previous treatments. The floor must be rinsed thoroughly by water. Apply two or three coats of **MIRAGLOSS** with applicator or mop evenly to the dry floor surface, allow each coat to dry before applying the next. About six months intervals, depending on traffic condition start a new maintenance cycle.
- Physical Properties** :
- | | |
|---------------|---------------------------|
| Appearance | : Opaque white liquid |
| PH (as is) | : 8.0 - 9.5 |
| Solid content | : 22.0 – 23.0% |
| Viscosity | : <60cps (#2/60rpm/26 °C) |



Distributor :
OCI SUPPLY SDN BHD
2018 0103 9495 (1301526-T)
22, JALAN 8/91, TAMAN SHAMELIN
PERKASA, JALAN CHERAS,
56100 KUALA LUMPUR, MALAYSIA.
TEL: +603 9283 9000
FAX: +603 9285 7570
EMAIL: sales1@ocisupply.com.my



Manufacturer:
OGOSIN CHEMICAL INDUSTRIES SDN BHD
1995 0103 0946 (360152 U)
No 11 Jalan Lombong Emas 4
Seremban Light Industrial Park
Jalan Tun Dr Ismail
70200 Seremban
Negeri Sembilan
Tel: 606-7611899 Fax : 606-7619819